

- Pulling rotation reduces the risk of sticking and kickback.
- Wet cutting capability, indoors and outdoors
- Ground-Fault Circuit Interrupter, GFCI
- Specially designed water nozzles
- Water governing valve
- Double insulated rotor
- Specially designed fan wheel
- SoftStart
- Microprocessor controlled over-load protection
- Well balanced power unit
- Professionally designed rear handle
- Ergonomically placed controls
- Build-in stop for easy blade change
- Motor bearing with special rubber seal
- Easily accessible carbon brushes

#### TECHNICAL DATA

---

##### Engine

Voltage 110 / 120 / 230 V

##### Cutting equipment

Blade diameter 350 mm / 14 inch

Max cutting depth 125 mm / 5 inch

##### Dimensions

Weight (excl. cutting equipment) 8.9 kg / 19.62 lbs

##### Vibration

Vibrations front handle 3.7 m/s<sup>2</sup>

Vibrations rear handle 4.2 m/s<sup>2</sup>

Daily Vibration Exposure (A8) 1.34 m/s<sup>2</sup>

Daily Vibration Time (Time factor) 1 h

Daily Vibration (Aeqv) 3.8 m/s<sup>2</sup>

##### Sound and noise

Sound level 95 dB(A)

Sound power level, LWA 108 dB(A)